



4031960

Studies have shown that as much as 50% of the air in your home comes up from your basement or crawlspace. This air is often higher in moisture content and carries with it various allergens and musty odors. When conditions linger above 60% relative humidity for extended periods of time, mold, mildew, and bacteria growth is stimulated.

The American Lung Association, American Medical Association, and the EPA recommend maintaining relative humidity levels in the 30% - 50% range. Ventilation and air conditioning alone cannot provide the protection offered by a high capacity dehumidifier like the Santa Fe Force.™ Protecting your family and your biggest investment is worth the best.

## "Application-Specific" Design

The Santa Fe Force features dual ducts that are specifically designed to provide the optimal amount of airflow in crawlspaces and basements. The optional condensate pump and duct kit can provide the installation flexibility necessary for almost any application. The Santa Fe Force is engineered for extremely quiet operation.

- **High Efficiency** – Exceeds ENERGY STAR® efficiency requirements.
- **Large Capacity** – The high capacity provides 120 pints per day of water removal at standard rating conditions\*. Large-sized basements and crawlspaces (up to 2900 sq. ft.) are no problem for the Santa Fe Force.
- **Low Temperature Operation** – Engineered for crawlspaces, and the temperature and air flow issues that they present. When many conventional dehumidifiers have stopped removing water from the air, the Santa Fe Force keeps on protecting you and your home.
- **Superior Air Filtration** – MERV-8 filtration is standard on the Santa Fe Force. This superior level of air filtration also keeps the unit working at peak efficiency and out performs other conventional dehumidifiers.
- **Auto Restart** – Santa Fe dehumidifiers will automatically restart at the original setting after a power outage.
- **Optional Equipment** – A duct kit and condensate pump are available for use with the Santa Fe Force. These optional kits provide the ultimate in flexibility for your specific installation requirements.

\*American Home Appliance Manufacturers (AHAM) standard testing conditions are 80°F and 60% RH.

## Consequences of High Humidity

- Wet crawlspaces and basements contribute to the cupping of wood floors and the deterioration of floor joists, beams, sub-flooring, insulation, and electrical-mechanical systems.
- Excess moisture encourages mold growth on wood and on any other organic material.
- Crawlspaces and basements are a major source of air infiltration that permeates up into the living area, transmitting odors, carrying moisture, and creating an environment conducive to molds, pests, and dust mite infestation.

## Crawlspace and Basement Dehumidification

The cooler temperatures in crawlspaces and basements create unique humidity control challenges for homeowners.

Capacities for residential dehumidifiers are measured in pints of water removed per day at standard conditions (80°F and 60% RH) determined by the American Home Appliance Manufacturers (AHAM). At these conditions, the capacity of the Santa Fe Force is 120 pints per day, while most standard residential units range from 20 to 65 pints of water removal per day. However, most basements and crawlspaces are cooler than 80°F and therefore the water removal capacity of the standard residential unit will be diminished significantly.

The Santa Fe Force is necessary to ensure that enough moisture is removed at the real-world temperature of your crawlspace or basement to prevent mold, mildew and bacterial growth. The Santa Fe Force is a dehumidifier designed for these cooler applications.



# Performance and Technical Specs

<b>Part Number:</b>	4031960
<b>Blower:</b>	365 CFM @ 0.0" WG
<b>Power:</b>	875 watts @ 80°F and 60% RH
<b>Supply Voltage:</b>	115 volt – 1phase – 60 Hz
<b>Current Draw:</b>	7.8 amps
<b>Operating Temp.:</b>	56°F Min., 95°F Max.
<b>Sized for:</b>	2900 Sq. Ft. - Typical
<b>Minimum Performance at 80°F and 60% RH</b>	
Water Removal:	120 Pints/Day
Efficiency:	5.7 Pints/kWh
Energy Factor:	2.7 L/kWh
<b>Air Filter:</b>	MERV-8
Efficiency:	Standard 65% Efficient, ASHRAE Dust Spot Test
Size:	Size: 1.75" x 14" x 17.5"
<b>Power Cord:</b>	8', 110-120 VAC, Ground
<b>Drain Connection:</b>	3/4" Threaded NPT
<b>Drain Hose:</b>	5/8" ID x 8'
<b>Dimensions</b>	<b>Unit</b>
Width:	14.5"
Height:	21"
Length:	26"
Weight:	90 lbs



The Santa Fe Force features dual duct outlets in order to maximize airflow in crawlspace and basement applications.

## Optional Accessories

4033035	MERV 8 Filter
4033036	MERV 8 Filters 4-Pack
4033037	MERV 8 Filters 12-Pack
4033038	Pump Kit
4026607	Caster Kit
4026450	Leveling Foot Kit
4033039	Supply Duct Kit (includes two 10" collars)
4026969	10" Flex Duct 25'
4022126	10" Insulated Flex Duct 25'
4020175	Remote Dehumidistat

The Santa Fe Force is designed for quiet operation and high capacity dehumidification.

### Remote Hygrometer



4029577

Displays indoor and outdoor temperature, relative humidity, moon phases, time and date.

Wireless sensor with low temperature adaptor included.

### CRAWLSPACE ALERT™



4030280

Works remotely with your Santa Fe Dehumidifier to provide a warning light when humidity levels are too high in the crawlspace and will automatically turn off the dehumidifier if the overflow safety switch is tripped on the condensate pump.



(401) 293-0422 or Toll Free (866) 865-0425  
 Email - [Info@OceanStateAir.com](mailto:Info@OceanStateAir.com)  
 Web Site: [www.OceanStateAir.com](http://www.OceanStateAir.com)



One of the best Limited Warranties in the industry today –

1 YEAR – All Parts and Labor  
 5 YEARS – Sealed Refrigeration System



**NAHB**  
 NATIONAL ASSOCIATION OF HOME BUILDERS



MEMBER